



APPLICATION: Provides Prominent & glare free Uniform illumination while repairing/maintainance of Industrial machines/equipments SPECIAL FEATURES: - Very sleek, rugged, Light weight design - Excellent glare free uniform light distribution - expected life span: 30,000 hrs - Very convenient, user friendly handle	BODY PARTS: -Aluminum extrusion/Heat sink has been been used to enhance LED life span -Handle: FR grade PVC -Rocker Switch for Mains Supply ON/OFF -Heavy duty Mains cord (5ft) -MCPCB for LED mounting -Total Weight:200 gm -Dimension (LxBxH):278mmx35mmx35mm
OPTICAL PARAMETERS: -Non yellowing diffuser -Uniform glare free distribution of light -Unbreakable Poly Carbonate Diffuser -LED Brand: Edison -CCT>6500K -CRI>80 -LUMEN:1200Lm -Beam angle=120 degree -Lumen efficacy=100Watt/Lumen -UV Free Light	ELECTRICAL PARAMETERS: -BIS approved premium quality Isolated LED Driver has been used -Mains Supply:170Vac-300Vac, 50Hz -Power consumption:12W -Power Factor PF>0.96, THD% < 15% -Efficiency (n) > 85% -Can withstand 440Vac -Auto short circuit Prot., Over Load Prot., and auto thermal shut down







*SPECIFICATIONS CAN BE CHANGED WITHOUT PRIOR NOTIFICATION DUE TO CONTINUOUS R&D.

> M:9925799688, E-mail: info@visiontechproducts.com Web site: www.visiontechproducts.com