



An ISO 9001:2015 Certified Co.


**VISION TECH<sup>®</sup>**  
**ELECTRONICS**



**PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR PLL/2X60W (UVC GERMICIDAL) LAMP (FOR MODEL:UV5:TUV PL-L 60W/4P HO , PHILIPS)**

**MODEL DESCRIPTION:**


Ballast Body Type: UV5  
LAMP:PLL/60W/UVC  
Cap: 2G11  
LAMP MAKE: PH (PHILIPS)



UV5: DIMENSION: L=278mm, W=55mm, H=42mm

**TECHNICAL SPECIFICATIONS:**

- TYPE: UV ELECTRONIC BALLAST/INDUSTRIAL FOR 2XPLL/60W/UVC, 2G11
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE:  $U_n = 170\text{Vac} - 300\text{Vac}$
- MAINS RATED VOLTAGE:  $V=230\text{Vac}$
- MAINS FREQUENCY:  $F_n(\text{Hz})=50\text{Hz}$
- MAINS I/P CURRENT:  $I_n=550\text{mA}$
- WATTAGE: 120W
- POWER FACTOR:  $PF > 0.95$
- SURGE PROTECTION DEVICE:  $SPD > 10\text{KV}$
- CREST FACTOR:  $CF > 1.70$
- AMBIENT TEMPERATURE:  $T_a=0...50^\circ\text{C}(\text{max})$ , CASE TEMPERATURE:  $T_c=55\text{C}(\text{max})$
- IN RUSH CURRENT PROTECTION, RFI/EMI PROTECTION
- TOLERANCE:  $\pm 5\%$



**FEATURES:**

- SLIM DESIGN
- BODY:METALLIC POWDER COATED
- MAINS LED INDICATOR:RED
- O/P GREEN LED INDICATORS SIGNIFY HEALTHY LAMPS/TUBES

**\*Due to continuous R&D, design can be changed without prior notification**

**\*Special Requirements will be entertained**

**WORKS/FACORY ADDRESS:**

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com