


An ISO 9001:2015 Certified Co.



VISION TECH[®]
ELECTRONICS



PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR

36W, Compact Soft Glass High Power HO UVC Germicidal Lamp (FOR MODEL: UV2-LTC35W 2G11 35W)

MODEL DESCRIPTION:

Ballast Body Type: UV2


LAMP: 36W, Compact Soft Glass Germicidal Lamp

Cap: 2G11

Make: LIGHT SOURCES



UV2: Dim. : LxBxH = 97mm x 46mm x 29mm



TECHNICAL SPECIFICATIONS:

- TYPE: COMPACT UVC ELECTRONIC BALLAST/INDUSTRIAL
- OPERATING VOLTAGE RANGE: $U_n = 170\text{Vac} - 300\text{Vac}$
- MAINS RATED VOLTAGE: $V=230\text{Vac}$
- MAINS I/P CURRENT: $I_N=170\text{mA}$
- WATTAGE: 36W
- POWER FACTOR: $PF > 0.90$
- SURGE PROTECTION DEVICE: $SPD > 4KV$
- CREST FACTOR: $CF < 1.70$
- TOLERANCE: $\pm 5\%$
- IN RUSH CURRENT PROTECTION
- RFI/EMI PROTECTION
- O/P DUAL LED:
 - .WHEN INDICATOR IS ORANGE, SIGNIFIES HEALTHY TUBE/LAMP
 - .WHEN INDICATOR IS RED, SIGNIFIES UNHEALTHY TUBE/LAMP

***Due to continuous R&D, design can be changed without prior notification**

***Special Requirements will be entertained**

WORKS/FACORY ADDRESS:

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com